

HOT SPOT<sup>®</sup> COLLECTION

# PACE<sup>™</sup>



5

Seats

24

Jets

300

Gallons

Double  
Lounge

Style

6'10" x 6'10" x 33"

Dimensions

115v/20 amp<sup>\*\*</sup>

Voltage

# PACE™



Pace spa shown with Alpine White shell, Havana Cabinet and Havana Everwood step.

### Spa Shell



Alpine White

Pearl

Pebble

Tuscan Sun

### Cabinet



Almond

Havana

Storm

### Spa Cover



Nutmeg

Stone

<b>Seating Capacity</b>	5 adults	<b>Control System</b>	IQ 2020® 115v/20 amp** (Includes G.F.C.I. protected power cord) or 115v/30amp*** or 230v/50amp***, 60Hz
<b>Dimensions</b>	6'10" x 6'10" x 33" / 2.08m x 2.08m x 0.84m	<b>Lighting (interior)</b>	10 multi-color LED points of light, dimmable
<b>Water Capacity</b>	300 gallons/1,135 liters	<b>Lighting (exterior)</b>	4 multi-color LED points of light, dimmable
<b>Weight</b>	775 lbs./350 kg dry; 4,150 lbs./1,880 kg filled*	<b>Heater</b>	No-Fault® 1000w/115v, or 4000w230v
<b>Spa Shell Options</b>	Alpine White, Pearl, Pebble or Tuscan Sun	<b>Energy Efficiency</b>	FiberCor® Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law
<b>Cabinet Options</b>	Almond, Havana, or Storm	<b>Effective Filtration Area</b>	30 sq. ft., top loading
<b>Jets - 24 (all with stainless steel trim)</b>	3 XL Directional Hydromassage jets 2 Directional Hydromassage jets 2 Rotary Hydromassage jets 17 Directional Precision® jets	<b>Vinyl Cover</b>	3.5" to 2.5" tapered, 2 lb. density foam core Nutmeg or Storm
<b>Jet Pump</b>	Wavemaster® 6200; Two-speed, 1.5 HP Continuous Duty, 3.2 HP Breakdown Torque	<b>Cover Lifter (Optional)</b>	CoverCradle®, CoverCradle II, or UpRite®
<b>Water Care System</b>	FROG® In-Line Cartridge Ready	<b>Steps (Optional)</b>	Everwood® Step - Almond, Havana, or Storm Polymer Step - Ash
<b>Ozone System (Optional)</b>	FreshWater® III Corona Discharge	<b>Entertainment System</b>	Wireless Sound System

Actual colors and products may vary from print representation. See dealer to verify. \* Includes water and 5 adults weighing 175 lbs. each. \*\*Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S. \*\*\* G.F.C.I. protected sub-panel required in 30amp conversion or 220v mode. Export models available in 230v, 50Hz, 1000w heater.