



Muriatic Acid

Commercial Grade

MURIATIC ACID is extremely corrosive. The purchaser assumes all responsibility for the safe transport, storage and handling of this product. The vendor is not responsible for damages resulting from misuse or careless handling.

Recommendations

To reduce the pH of swimming pool water:

Test water to determine amount of acid needed. Carefully pour acid in small quantities in several locations directly into the pool. Circulate pool water for 1-2 hours prior to re-testing and possible further additions.

To clean or etch concrete and masonry:

Dilute acid to desired strength. Rinse area with water. Apply acid with nylon brush. Rinse well with clean water.

To descale porcelain, glazed tile and to clean metal:

Mix acid with equal parts of water. Test strength on small area prior to overall application. Rinse area with water. Apply acid with nylon brush. Rinse well with clean water.

To remove white efflorescence from brick:

Mix one part acid with three parts water. Test strength on small area prior to overall application. Rinse area with water. Apply acid with nylon brush. Rinse well with clean water.

Notes

- Always add acid to water, never add water to concentrated acid.

Physical Properties

Appearance: Light yellow

Fragrance: Pungent

Specific Gravity: 1.16

pH: Less than 1.0

Code	Size	Special notes
01010C11	4 x 4 L	
01010P93	20 L pail	
01010D80	205 L drum	

REVD150714