

HIGHLIFE[®] COLLECTION





6'8" x 7'9" x 33"

FreshWater® Salt System Ready

Dimensions

Water Care

HIGHLIFE® COLLECTION SOVEREIGN®







Chocolate Smoke

Cabinet and Shell Color Options*

Cabinet Colors	Walnut	Bronze	Sandstone	Driftwood	Brushed Nickel	Shale
Shell Colors	Alpine White Ivory Ice Gray Tuscan Sun Desert	Alpine White Ivory Tuscan Sun Desert	Alpine White Ivory Tuscan Sun Desert	Alpine White Ice Gray Tuscan Sun Platinum	Alpine White Ice Gray	Alpine White Ice Gray Platinum

Seating Capacity	6 people	Lighting System	Luminescence® multi-color four-zone			
Dimensions	6'8" x 7'9" x 33" / 2.03 m x 2.36 m x 0.84 m	Heater	Titanium No-Fault® 6,000 W / 230 V			
Water Capacity	315 gallons / 1,200 liters	Energy Efficiency	Multiple Layers of Foam Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas			
Weight	610 lbs. / 275 kg dry; 4,290 lbs. / 1,945 kg filled**					
Jets	28 total • 1 Moto-Massage® DX jet • 2 SoothingStream® jets	Filtration System	100% no-bypass filtration, top loading Tri-X® filters, 195 sq. ft. effective filtration area			
	 1 JetStream[®] jet 2 Rotary Hydromassage jets 	Vinyl Cover	with hinge seal in Chocolate or Smoke			
	 3 Directional Hydromassage jets 18 Directional Precision[®] jets 	Available Options				
Water Feature	BellaFontana® with 3 illuminated arcs of water	Cover Lifter	CoverCradle®, CoverCradle II, Lift 'n Glide® or UpRite®			
Jet Pump	Wavemaster [®] 9200; Two-speed, 2.5 HP Continuous Duty,	Steps Highlife Collection Step (Cocoa or Smok				
	5.2 HP Breakdown Torque	Entertainment	Bluetooth® Wireless Sound System			
Circulation Pump	SilentFlo 5000® for quiet, continuous filtration					
Water Care System	FreshWater® Salt System Ready					
Control System	IQ 2020® with wireless remote control 230 V / 50 amp, 60 Hz					

*No special orders or shell substitutions available. Actual colors and products may vary from print representation. See dealer to verify. **Includes water and 6 adults weighing 175 lbs. each. Export models available in 240 V, 50 Hz, 2,000 W heater.

(Includes G.F.C.I. protected sub-panel)