


FreshWater® IQ System Ready



Dual Action Filtration
SilentFlo Circulation



FiberCor® High-Density Insulation



Color LCD Display

LIMELIGHT® COLLECTION

BEAM



PeopleSeatingJetsVoltage4 SeatsOpen19 Jets115 or 230 V

Size

6'8" x 6'8" x 33" | 203 cm x 203 cm x 84 cm

Water Care

FreshWater®IQ System Ready



LIMELIGHT® COLLECTION

BEAM





SHELL COLORS*











Alpine

Platinum Desert

Tuscan Sun

CABINET COLORS*







Coastal Gray

Sable

Espresso

COVER COLORS

POLYESTER





Storm

LEGENDARY MASSAGE

19 Personalized-Control Jets

• 1 XL Dual Rotary jet

• 2 Standard Single Rotary jets

• 2 Standard Directional jets

• 14 Directional Precision® jets

EASY WATER CARE

Water Care System FreshWater®IQ System Ready

Smart Monitoring System Optional

Filtration System Dual action, 100 sq. ft., top loading

LEADING ENERGY EFFICIENCY

Jet Pump Beam I

Wavemaster® 7000; Two-speed, 1.65 HP Continuous Duty,

3.5 HP Breakdown Torque

Beam II

Wavemaster® 9000; Two-speed, 2.5 HP Continuous Duty,

5.2 HP Breakdown Torque

SilentFlo 5000® for quiet, continuous filtration **Circulation Pump**

Heater Beam I

Titanium No-Fault $^{\odot}$ 1,500 W / 115 V or 6000w / 230v

Beam II

Titanium No-Fault® 6,000 W / 230 V

FiberCor® Insulation; Certified to California Insulation

> Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas

Cover WeatherPro™ 4" Tapered Custom-Fit with Hinge Seal

SIZE

Dimensions 6'8" x 6'8" x 33" / 203 cm x 203 cm x 84 cm

CAPACITY

Seating Capacity 4 seats

295 gallons / 1,115 liters **Water Capacity**

Weight 700 lbs. / 320 kg dry; 3,860 lbs. / 1,750 kg filled**

ADDITIONAL FEATURES

Smart Spa

Hot Spring Spas App, Powered by the Connected Spa Kit

Technology*

Water Feature Vidro® backlit ribbon waterfall

Cover Lifters*

CoverCradle®, CoverCradle II, Lift 'n Glide®, or UpRite®

Steps*

Limelight Collection Step (Coastal Gray, Espresso, and Sable), Polymer Step (Ash)

Entertainment*

Bluetooth® Wireless Sound System

Control System Beam I

IQ 2020® with LCD control panel

115 V / 20 amp, 60 Hz (Includes G.F.C.I. protected power cord)

or 230 V / 50 amp, 60 Hz

Beam II

CoolZone™

IQ 2020® with LCD control panel

230 V / 50 amp, 60 Hz (Includes G.F.C.I. protected sub-panel)

Lighting System

Raio® multi-color interior points of light Exterior multi-color lighting with timer

Cooling System*

*Optional Accessories