

## Highlife® Collection NXT



Jetsetter NXT shown with Alpine White shell



Jetsetter NXT shown with Alpine White shell / Mocha cabinet

## Jetsetter® NXT

### Specifications

<b>Seating Capacity</b>	3 adults
<b>Dimensions</b>	7' x 5'5" x 33"/2.13m x 1.65m x .84m
<b>Water Capacity</b>	225 gallons/852 liters
<b>Weight</b>	480 lbs./217 kg dry; 2,882 lbs./1,307 kg filled*
<b>Spa Shell Options</b>	Alpine White, Crème, Ice Gray, Tuscan Sun or Desert**
<b>Cabinet Options</b>	Everwood®HD: Mocha, Monterey Gray or Teak**
<b>Jets - 22 (w/ Stainless Steel Trim)</b>	1 Moto-Massage® DX jet (2) 1 JetStream® jet 2 Rotary Hydromassage jets 1 Directional Hydromassage jet 4 HydroStream® jets 12 Directional Precision® jets
<b>Water Care System (Optional)</b>	ACE® Salt Water Sanitizing System or EverFresh® System
<b>Jet Pump</b>	Wavemaster® 9000; One-speed, 2.5 HP Continuous Duty, 5.2 HP Breakdown Torque
<b>Circulation Pump</b>	SilentFlo 5000® for quiet, continuous filtration
<b>Effective Filtration Area</b>	195 sq. ft., top loading Tri-X® filters, 100% no-bypass filtration
<b>Ozone System</b>	FreshWater® III Corona Discharge
<b>Control System</b>	IQ 2020® with wireless remote control, 230v/50amp, 60Hz, Includes G.F.C.I. protected sub-panel***
<b>Lighting System</b>	Luminescence® multi-color four-zone
<b>Heater</b>	No-Fault®, 6000w/230v
<b>Energy Efficiency</b>	Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law
<b>Vinyl Cover</b>	3.5" to 2.5" tapered 1.5 lb. density foam core, with hinge seal in Caramel, Slate, Chocolate or Evergreen
<b>Cover Lifter (Optional)</b>	CoverCradle®, CoverCradle II, Lift 'n Glide® or UpRite®
<b>Steps (Optional)</b>	Everwood® HD, NXT or Polymer
<b>Entertainment System (Optional)</b>	Wireless Sound System

\* Includes water and 3 adults weighing 175 lbs. each

\*\* Some color combinations are considered special orders. Ice Gray/Teak, Crème/Monterey Gray, and Desert/Monterey Gray have special order pricing. See your dealer for details.

\*\*\* G.F.C.I. Protected sub-panel required in 230v mode

Export models available in 230v, 50Hz, 1500w Heater